


ProCeas[®] Air

N₂O, CH₄, CO₂, NH₃ and H₂O, OFCEAS laser analyzer

- Sensitivity down to ppb
- Continuous measurement over the 5 gases
- Fast response time



Features

- Continuous measurement
- Multi components
- High resolution laser technology
- Patented OFCEAS IR laser technology
- No optical moving parts
- Patented Low Pressure Sampling system
- No compressed air consumption
- Maintenance: yearly

Benefits

- Measurement without interference regardless of the matrix
- High sensitivity
- Self-calibrating system (no span gases required)
- Very fast response time
- Ultra-precise measurement
- Negligible drift
- High availability of the system
- No water condensation from sampling point to analyzer due to Low Pressure Sampling

Technical data

Analyzer (1/2)	
Technique	OFCEAS
Power supply	110 ... 230 VAC, 50 ... 60 Hz
Power consumption	150 W (max), 80 W (average)
Dimensions	Rack 19", 4U
Weight	20 kg
Data outputs	Ethernet, ModBus (TCP/IP, RS), analog, USB

Analyzer (2/2)	
Fittings	1/4" or OD6
Pumping system	External Closed loop (optional)
Sample conditions	-40 ... 50 °C (temperature) <99% RH non-condensing Atm +/-100 mbar (pressure) 0.2 slm, 0.33 slm (for NH ₃)
Ambient conditions	10 ... 40 °C (temperature) <99% RH non-condensing

Performance specifications (N ₂ O, CH ₄ , CO ₂ , NH ₃ and H ₂ O, in ambient air)						
Gas		N ₂ O	CH ₄	CO ₂	NH ₃	H ₂ O
Lower detection limit (3σ, 300 s)		<6 ppb	<6 ppb	<500 ppb	<6 ppb	<360 ppm
Precision (1σ)	1 s	5 ppb + 0.1% of reading	5 ppb + 0.1% of reading	300 ppb + 0.1% of reading	<5 ppb	<300 ppm
	10 s	4 ppb + 0.1% of reading	4 ppb + 0.1% of reading	1 ppb + 0.1% of reading	<4 ppb	<200 ppm
	300 s	2 ppb + 0.1% of reading	2 ppb + 0.1% of reading	180 ppb + 0.1% of reading	<2 ppb	<120 ppm
Measurement interval		1 s	1 s	1 s	1 s	1 s
Response time / fall time (10 ... 90%)		<2 s	<2 s	<2 s	<30 s	<30 s
Measurement range	Guaranteed Operational	0.1 ... 200 ppm 0 ... 400 ppm	1 ... 15 ppm 0 ... 20 ppm	300 ... 5 000 ppm 0 ... 2% vol	0 ... 1000 ppb 0 ... 10 ppm	0 ... 3% vol 0 ... 5% vol
Cross-sensitivity on N ₂ O	No cross-sensitivity with CO ₂ (up to 5% vol), CH ₄ (up to 500 ppm), NH ₃ (up to 10 ppm), C ₂ H ₆ (up to 200 ppm), C ₂ H ₄ (up to 50 ppm) and C ₂ H ₂ (up to 20 ppm)					

AP2E

Parc de la Duranne – Les Méridiens | Bât. A – 240 rue Louis de Broglie – CS. 90537 | 13593 Aix-en-Provence Cedex 3
Phone +33 4 42 61 29 40 | info@ap2e.com | www.ap2e.com